

BASIC SPECIFICATIONS:

Configuration:	Workgroup Network Black & White Printer with Standard Duplex, 500 Sheet Drawer plus 100 Sheet Multi-Purpose Tray
Resolution:	Fine 1200 mode (1200 x 1200 dpi), Fast 1200 mode (1800 x 600 dpi), 600 x 600 dpi, 2400 x 600 dpi Interpolated (w/KIR)
Printer Memory:	Standard 128MB, upgradable to 640MB via 100 pin DDR DIMMs; Standard CF Card Slot (Type 1), MicroDrive Slot
Electrical Requirements:	120V, 60Hz, 7.7A
Dimensions:	15.04"W x 15.51"D x 12.60"H
Weight:	37.04 lbs
Max Duty Cycle:	250,000 Pages per Month

CONTROLLER SPECIFICATIONS:

Controller:	PowerPC750/500 Mhz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (XL, 5e, PJI), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24E, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL6/KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003/Vista
Novell® OS Compatibility:	Novell Network® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX Interface, Hi-Speed USB 2.0, USB Host (Full), Parallel IEEE1284
KUIO LV Enhancement Slot:	Optional IB-23 Secure NIC; Optional IB-11 Serial Interface
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Drivers:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KMnet Admin, KM-NET Viewer, PDF Direct Print
Web Interface:	Kyocera Command Center

OPTIONAL SECURE NETWORK INTERFACE: IB-23

Optional Network Interface supports IPv6, Security and Compliance	
Security Protocols:	SSL/TLS(HTTPS); SNMPv3

OUTPUT SPEEDS:

Warm-Up Time:	Less than 15 Seconds (From Sleep Mode)
First Print Out:	Less than 9 Seconds (EcoFuser Off)
Pages Per Minute:	47 Letter, 38 Legal

PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", Oficio2, A4, A5, B5, A6, Folio
MPT Paper Size:	8.5" x 11", 8.5" x 14", Oficio2, A4, A5, B5, A6, Folio Custom (2.8" x 5.8" - 8.5" x 14.0")
Std/Max Paper Capacity:	600 Sheets/2,500 Sheets
Paper Weight:	16 - 32 lb Bond via Paper Drawer, 16 lb Bond - 120 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

STANDARD DUPLEX:

Type:	Embedded Stackless Duplex
Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Paper Weight:	16 - 28 lb Bond

PAPER HANDLING OPTIONS:

PAPER DRAWER: PF-310

Paper Capacity:	500 Sheets
Paper Weight:	16 - 32 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", Oficio2, A4, A5, B5, A6, Folio
Dimensions/ Weight:	15.04"W x 15.51"D x 4.33"H / 8.6 lbs

PAPER FEEDER: PF-315

Paper Capacity:	2,000 Sheets
Paper Weight:	16 lb Bond - 110 lb Index
Paper Size:	8.5" x 11", A4, B5
Dimensions / Weight:	13.58"W x 14.80"D x 13.86"H / 16.53 lbs

ENVELOPE FEEDER: EF-310

Paper Size:	Monarch; Commercial 6 ¾, 9, 10; International DL, C5
Paper Weight:	16 to 24 lb Bond
Envelope Capacity:	1.5" or 40mm
Dimensions/ Weight:	10.75"W x 7.01"D x 4.61"H / 1.65 lbs

FACE UP TRAY: PT-310

Paper Size:	8.5" x 11", 8.5" x 14", Oficio2, A4, A5, B5, A6, Folio
Paper Weight:	16 lb Bond - 120 lb Index
Paper Capacity:	250 Sheets
Dimensions / Weight:	9.84"W x 12.99"D x 2.76"H / 0.63 lbs

ADDITIONAL OPTIONS:

Additional memory is available in 64, 128, 256, or 512 MB DDR DIMMs

CONSUMABLES:

EPT-470:	20,000 pages @ 5% Coverage*
	* Ships with 10,000 pages @ 5% Coverage. ISO 19752 Certified

Kyocera's objective is to manufacture superior products with a low Total Cost of Ownership (TCO), and have little or no impact on the environment. Kyocera's ECOSYS® Technology provides customers with a printing solution that incorporates long life consumables and one of the lowest costs per print in the industry.

The EcoPro product line is designed to provide maximum performance at a significant cost savings. The operating costs of traditional printers can easily exceed many times the original purchase price during the life of the products. Evaluate your printer costs today. Look into EcoPro and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceraecopro.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc.
Headquarters: 225 Sand Road,
PO Box 40008, Fairfield, NJ
07004-0008, USA
©2007 Kyocera Mita America, Inc.

