

BASIC SPECIFICATIONS:

| | |
|--------------------------|---|
| Configuration: | Color Tandem Network Printer with Standard 500 Sheet Drawer, 100 Sheet Multi-Purpose Tray, Optional Duplexing, Optional Paper Drawer and Hard Disk Drive. |
| Resolution: | 600 x 600 dpi (Multi-bit) |
| Printer Memory: | Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card Slot. (Type 1) Optional Hard Disk Drive |
| Electrical Requirements: | 120V, 60Hz, 9.5A |
| Dimensions: | 13.6"W x 18.5"D x 15.2"H |
| Weight: | 52.9 lbs |
| Max Duty Cycle: | 50,000 Pages per Month |

CONTROLLER SPECIFICATIONS:

| | |
|-------------------------------|--|
| CPU/MHz: | Embedded PowerPC750CXR/400MHz |
| Supported PDL / Emulations: | PRESCRIBE, KPDL3 (PS3), PCL 6 (PCL 5c, PCL XL) |
| Fonts: | 80 Outline Fonts for KPDL3 and PCL 5c/XL, 1 Bitmap Font |
| Windows® OS Compatibility: | Windows® 95/98/Me/NT4.x/2000/XP/Vista |
| Novell® OS Compatibility: | Novell NetWare® 3.x/4.x/5.x/6.x |
| Mac OS Compatibility: | OS 8.x/9.x/10.x |
| UNIX OS Compatibility: | Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR) |
| Connectivity / Interface: | Standard 10/100 BaseTX, Hi-Speed USB 2.0 |
| KUIO LV Enhancement Slot (1): | Optional IB-23 Secure NIC; Optional IB-11 Serial Interface; Optional Printer Hard Disk Drive |
| Supported Protocols: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI |
| Drivers: | KX Driver for Windows®, PPD for Mac, PPD for Linux/Unix, Certified Uni Driver, Windows® 64-bit Drivers |
| Utilities: | KMnet Admin, KM-NET Viewer, PDF Direct Print |
| Web Interface: | Kyocera Command Center |

OPTIONAL SECURE NETWORK INTERFACE: IB-23

| | |
|----------------------------|--|
| Optional Network Interface | supports IPv6, Security and Compliance |
| Security Protocols: | SSL/TLS(HTTPS); SNMPv3 |

PAPER SUPPLY:

| | |
|-------------------------|---|
| Standard Paper Sources: | 500 Sheet Drawer, 100 Sheet MPT |
| Drawer Paper Size: | 8.5" x 11", 8.5" x 14", A4, A5, B5 |
| MPT Paper Size: | 8.5" x 11", 8.5" x 14", A4, A5, B5, Custom (2.8" x 5.8" - 8.5" x 14") |
| Min/Max Paper Capacity: | 600/1,100 Sheets |
| Maximum Paper Sources: | Three |
| Paper Weight: | 16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes |

OUTPUT SPEEDS:

| | |
|--------------------------------------|-------------------------------------|
| Warm-Up Time: | Within 80 Seconds |
| First Print Out Color: | 16 Seconds |
| First Print Out Monochrome: | 16 Seconds |
| Pages Per Minute (Color/Monochrome): | 17/17 Letter, 16/16 A4, 14/14 Legal |

PAPER HANDLING OPTIONS:

DUPLEX UNIT: DU-301

| | |
|----------------------|------------------------------------|
| Paper Size: | 8.5" x 11", 8.5" x 14", A4, A5, B5 |
| Paper Weight: | 16 - 28 lb Bond |
| Dimensions / Weight: | 13.6"W x 22"D x 9.7"H / 12.3 lbs |

PAPER DRAWER: PF-60

| | |
|--------------------|------------------------------------|
| Paper Capacity: | 500 Sheets |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 8.5" x 11", 8.5" x 14", A4, A5, B5 |
| Dimensions/Weight: | 13.6"W x 17.8"D x 4.1"H / 8.4 lbs |

FACE-UP TRAY: PT-300

| | |
|-----------------|--|
| Paper Capacity: | 250 Sheets for Printer, 100 Sheets for Duplexer (DU-301) |
|-----------------|--|

OPTIONAL HARD DISK DRIVE:

| | |
|--|---|
| Enables Document Printing and e-MPS Functions: | Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes |
|--|---|

CONSUMABLES:

| | | |
|---|-----------------|---------------------------|
| EPT-170K: | Black Toner* | 6,000 Pages @ 5% Coverage |
| EPT-170Y: | Yellow Toner** | 4,000 Pages @ 5% Coverage |
| EPT-170M: | Magenta Toner** | 4,000 Pages @ 5% Coverage |
| EPT-170C: | Cyan Toner** | 4,000 Pages @ 5% Coverage |
| * Ships with 3,000 pages @ 5% Coverage. ISO 19752 Certified | | |
| ** Ships with 2,000 pages @ 5% Coverage. | | |

Kyocera's objective is to manufacture superior products with a low Total Cost of Ownership (TCO), and have little or no impact on the environment. Kyocera's ECOSYS® Technology provides customers with a printing solution that incorporates long life consumables and one of the lowest costs per print in the industry.

The EcoPro product line is designed to provide maximum performance at a significant cost savings. The operating costs of traditional printers can easily exceed many times the original purchase price during the life of the products. Evaluate your printer costs today. Look into EcoPro and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceraecopro.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc.
Headquarters: 225 Sand Road,
PO Box 40008, Fairfield, NJ
07004-0008, USA
©2007 Kyocera Mita America, Inc.

